

Remove 9001 Powder Coat Remover-Gel

T E C H N I C A L D A T A S H E E T

Description: Remove 9001 Room Temperature Powder Coat Remover- Gel is a Non-Hazardous, Ready-to-Use Powder Stripper that Dissolves Powder Coatings, Epoxy, Autodeposition Coatings, Varnishes & Adhesives. Operator Friendly, Non-Caustic, Non- Acid, Low-Odor Formula.

Directions: Remove 9001 Dissolves Powder Coat in 15 minutes to 1-2 hours at Room Temperature in an immersion tank, drum or pail. It's Aluminum & All Metal Safe. Formulated to Clean Powder Coating from Hooks, Racks and Coating Rework at Room Temperature . Strip time will vary depending on type of coating and coating film build. Mechanical Agitation is not required, however will accelerate stripping. Air agitation is not recommended: Air-(Oxygen will reduce solution life). Use No-Water with Remove 9001. Rinse parts with water after stripping.

Warning: May be harmful if swallowed. May cause skin and eye irritation. Eye protection and rubber gloves are recommended when handling this product.

First Aid: In case of eye or skin contact flush with large amounts of water for 15 minutes. If irritation persists, see physician. In case of ingestion, do not induce vomiting; drink large quantities of water to dilute product. Get medical attention at once.

Hazard Class: Non-regulated

<i>Properties:</i>	pH:	11.5 - 12.5	Health:	1
	Specific Gravity:	1.03 - 1.05	Flammability:	1
	Color:	Amber	Reactivity:	0